

MICHELIN INFLATION CHARTS FOR LIGHT TRUCK TIRES

To select the proper load and inflation table, locate your tire size in the following pages, then match your tire's sidewall markings to the table with the same sidewall markings. If your tire's sidewall markings do not match any table listed, please contact your MICHELIN dealer for the applicable load and inflation table.

Industry load and inflation standards are in a constant state of change, and Michelin continually updates its product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration, or 2 tires per axle.

D = Dual configuration, or 4 tires per axle.

Loads are indicated per axle.

WHEEL DIAMETER 15"	PSI	35	40	45	50	55	60	65	70	75	80	MAX LOAD & PRESSURE ON SIDEWALL	
	kPa	250	280	310	350	380	410	450	480	520	550		
LT235/75R15 LRC LTX M/S	LBS SINGLE	3060	3360	3650	3970							S	1985 LBS AT 50 PSI
	LBS DUAL	5560	6120	6640	7280							D	1820 LBS AT 50 PSI
	KG SINGLE	1420	1525	1655	1800							S	900 KG AT 350 KPA
	KG DUAL	2580	2775	3010	3300							D	900 KG AT 350 KPA

WHEEL DIAMETER 16"	PSI	35	40	45	50	55	60	65	70	75	80	MAX LOAD & PRESSURE ON SIDEWALL	
	kPa	250	280	310	350	380	410	450	480	520	550		
LT215/85R16 LRE LTX A/S, LTX A/T2, LTX M/S, XPS RIB, XPS TRACTION	LBS SINGLE	2990	3280	3570	3880	4100	4360	4670	4860	5100	5360	S	2680 LBS AT 80 PSI
	LBS DUAL	5440	5960	6500	7060	7460	7940	8600	8840	9280	9880	D	2470 LBS AT 80 PSI
	KG SINGLE	1990	1488	1619	1760	1860	1978	2120	2205	2313	2430	S	1215 KG AT 550 KPA
	KG DUAL	2520	2703	2948	3200	3384	3602	3900	4010	4209	4480	D	1120 KG AT 550 KPA
LT225/75R16 LRE LTX A/S, LTX A/T2, LTX M/S, XPS RIB	LBS SINGLE	3000	3300	3580	3880	4120	4380	4670	4880	5120	5360	S	2680 LBS AT 80 PSI
	LBS DUAL	5460	6000	6520	7060	7500	7980	8600	8880	9320	9880	D	2470 LBS AT 80 PSI
	KG SINGLE	1400	1500	1625	1760	1870	1990	2120	2215	2320	2430	S	1215 KG AT 550 KPA
	KG DUAL	2540	2720	2960	3200	3400	3620	3900	4030	4230	4480	D	1120 KG AT 550 KPA
LT235/85R16 LRE LTX A/T2, LTX M/S, XPS RIB, XPS TRACTION	LBS SINGLE	3400	3740	4060	4410	4670	4970	5246	5530	5810	6084	S	3042 LBS AT 80 PSI
	LBS DUAL	6180	6800	7380	8024	8500	9040	9524	10060	10580	11112	D	2778 LBS AT 80 PSI
	KG SINGLE	1580	1696	1842	2000	2118	2254	2380	2508	2635	2760	S	1380 KG AT 550 KPA
	KG DUAL	2880	3084	3348	3640	3856	4100	4320	4563	4799	5040	D	1260 KG AT 550 KPA
LT245/75R16 LRE LTX A/T2, LTX M/S, XPS RIB	LBS SINGLE	3400	3730	4060	4410	4670	4960	5250	5530	5800	6084	S	3042 LBS AT 80 PSI
	LBS DUAL	6180	6780	7380	8024	8500	9020	9525	10060	10560	11112	D	2778 LBS AT 80 PSI
	KG SINGLE	1580	1690	1840	2000	2120	2250	2380	2510	2630	2760	S	1380 KG AT 550 KPA
	KG DUAL	2880	33075	3350	3640	3855	4090	4320	4560	4790	5040	D	1260 KG AT 550 KPA
LT265/75R16 LRC LTX A/T2	LBS SINGLE	3820	4200	4560	4940							S	2470 LBS AT 50 PSI
	LBS DUAL	6960	7640	8300	8600							D	2270 LBS AT 50 PSI
	KG SINGLE	1780	2020	2240	2240							S	1120 KG AT 350 KPA
	KG DUAL	3600	4120	4600	3900							D	1030 KG AT 350 KPA
LT265/75R16 LRE LTX M/S	LBS SINGLE	3820	4200	4560	4940	5250	5580	6000	6210	6520	6830	S	3415 LBS AT 80 PSI
	LBS DUAL	6960	7640	8300	9080	9560	10160	11020	11300	11860	12340	D	3085 LBS AT 80 PSI
	KG SINGLE	1780	1905	2070	2240	2380	2530	2720	2815	2960	3100	S	1550 KG AT 550 KPA
	KG DUAL	3240	3465	3765	4120	4340	4610	5000	5125	5380	5600	D	1400 KG AT 550 KPA

Commercial Light
Truck Tires